

# nn\_example

April 12, 2017

```
In [1]: from __future__ import division, print_function

import numpy as np
import tensorflow as tf
import utilities
```

## 1 Initialization

```
In [2]: graph = tf.Graph()
        sess = tf.InteractiveSession(graph=graph)

In [3]: x0 = tf.placeholder(tf.float64, [None, 1], name='input_data')

In [4]: W1 = tf.Variable(np.array([[1],
                                   [-1]], dtype=np.float64),
                        name='W1')

        W2 = tf.Variable(np.array([[1, 1],
                                   [5, 2]], dtype=np.float64),
                        name='W2')
```

## 2 Define graph/network

```
In [5]: def relu(x, weights, name='relu'):
        with tf.variable_scope(name):
            # Equivalent to weights.dot(x), but x can be
            # a row-vector with multiple entries
            m = tf.matmul(x, weights, transpose_b=True)
            return tf.maximum(m, 0.)

In [6]: x1 = relu(x0, W1, name='F1')
        x2 = relu(x1, W2, name='F2')

        y = x2
        y1, y2 = tf.split(y, 2, axis=1, name='split_y1_y2')

In [7]: utilities.show_graph(graph)
```

<IPython.core.display.HTML object>

### 3 Run network

```
In [8]: x_data = np.array([[1.]])
        feed_dict = {x0: x_data}

        sess.run(tf.global_variables_initializer())

In [9]: # Evaluate output
        sess.run(y, feed_dict=feed_dict)

Out[9]: array([[ 1.,  5.]])

In [10]: # Evaluate gradient
         g1 = tf.gradients(y1, W1)
         g2 = tf.gradients(y1, W2)

         grad1, grad2 = sess.run((g1, g2), feed_dict=feed_dict)

         print(grad1, grad2, sep='\n')

[array([[ 1.],
        [ 0.]])
array([[ 1.,  0.],
        [ 0.,  0.]])]
```

```
In [ ]:
```